BATTERY OPERATED CONTROLLERS COMPARISON CHART

No Power, No Problem

Battery operated controllers allow irrigation to occur without tapping into an electrical connection. They still maintain most of the user-friendly features provided by their wired counterparts.









	втт	NODE	NODE-BT	XC HYBRID
QUICK SPECS				
MAX NUMBER OF STATIONS	2	6	4	12
VALVE WIRE OPTIONS	Diaphragm Valve	Conventional	Conventional	Conventional
NUMBER OF PROGRAMS	2	3	3	3
START TIMES PER PROGRAM	4	4	8	4
TYPE*	Fixed	Fixed	Fixed	Fixed
WARRANTY	2 Years	2 Years	2 Years	2 Years
FEATURES				
ENCLOSURE TYPE	Plastic Indoor/Outdoor	Plastic, Waterproof	Plastic, Waterproof	Plastic Indoor/Outdoor Stainless Indoor/Outdoor
SOLAR SYNC ET SENSOR COMPATIBLE	No	No	No	No
CENTRAL CONTROL COMPATIBLE	No	No	No	No
REMOTE CONTROL COMPATIBLE	Yes (Smart Phone)	No	Yes (Smart Phone)	No
FLOW SENSOR COMPATIBLE	No	No	No	No
RAIN/FREEZE SENSOR COMPATIBLE	No	Yes	Yes	Yes
SOIL SENSOR COMPATIBLE	No	No	Yes	No
NUMBER OF SENSOR INPUTS	0	1	2	1
MAX STATION RUN TIME (HRS)	24	6	18	4
APPLICATION				
RESIDENTIAL	•	•	•	•
LIGHT COMMERCIAL		•	•	Ø
COMMERCIAL		•	•	•