

MCC

Expand the limits of irrigation control with wireless, wide-area coverage for large-scale projects.

KEY BENEFITS

- Medium commercial controller
- Supports conventional, EZDS two-wire, and wireless outputs
- Advanced flow management and monitoring
- Up to 3 flow sensor inputs
- Multiple repeaters supported, with multiple WVOMs on different channels
- Up to 8 simultaneous stations plus up to 3 Pump/Master Valves

PRODUCT SPECIFICATIONS

MCC-800-M, MCC-800-SS Metal Wall Mount

- Height: 41.9 cm
- Width: 35.0 cm
- Depth: 16.3 cm

MCC-800-P Plastic Wall Mount

- Height: 44.9 cm
- Width: 36.6 cm
- Depth: 16.3 cm

Both models are supplied with a separate wall-mounting plate and hardware.

Enclosure Ratings: Steel Wall Mounts IP55, Plastic Wall Mounts IP55, Plastic Pedestals IP24

ELECTRICAL SPECIFICATIONS

- Transformer input: 120/230 VAC, 50/60 Hz
- Max AC current draw: 120 VAC, 2A; 230 VAC, 1A
- Transformer output: 3 A
- P/MV outputs (24 VAC): 800 mA

Communication Options

- Wi-Fi: 2.4 GHz, 802.11n
- LAN: Ethernet RJ-45, 100 Mbps
- Cell: 4/5G LTE

APPROVALS

UL, CE, cUL, RCM, FCC

ADDITIONAL SPECIFICATIONS

Station outputs: Up to 108 stations (54 conventional, 108 in any combination with EZ-DM and WVOM)



Copyright © 2026 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://www.hunterirrigation.com/en-metric/irrigation-product/controllers/mcc062626>