PRO-C HYDRAWISE

Number of Stations: 4 - 16

Type: Modular

FEATURES

- Wi-Fi-enabled for easy connection to the internet from any location
- Uses Hydrawise web-based software to offer automatic watering schedule updates
- · Integrates local weather data to make water-saving schedule adjustments
- Utilizes Pro-C modules to create station counts between 4-16
- · Built-in milliamp sensor
- · Roam and Roam XL compatible
- · Warranty: 2 years
- ► Touch-screen interface
- ► Predictive Watering[™] adjustments
- ▶ Flow meter detection and alerts with optional HC Flow meter
- Wiring detection and alerts
- ▶ Includes 1.5 m lead and plug

ELECTRICAL SPECIFICATIONS

- Transformer input: 230 VAC
- Transformer output (24 VAC): 1 A
- Station output (24 VAC): 0.56 A
- P/MV: (24 VAC): 0.28 A
- Sensor inputs: 1



- CE, UL, cUL, C-tick, FCC
- ► = Advanced Feature descriptions on pagepage 88

PRO-C HYDRAWISE		
Model	Description	
HPC-400	4-station base: Domestic 110 VAC indoor/outdoor controller	
HPC401E	4-station base: European 230 VAC indoor/outdoor controller	
HPC401A	4-station base: Australian 230 VAC indoor/outdoor controller	

PC-SERIES STATION EXPANSION		
Model	Description	
PCM-300	3-station plug-in module: Use to increase station count from 4 to 7, 10, or 13	
PCM-900	9-station plug-in module: Use to increase station count from 7 to 16	

HPC FACE PANEL	
Model	Description
HPC-FP	Hydrawise retrofit front panel for Pro-C controllers



Plastic Indoor/Outdoor

Height: 23 cm Width: 21.5 cm Depth: 10.9 cm



HPC Face Panel



PCM-300 and PCM-900 Expansion Modules



Smart WaterMark

Recognized as a responsible water-saving tool.