



POZ	
Ref.	description
IGPOZ2000N01C	MINI circular
IGPOZ2000NA2C	LARGE circular
IGPOZ2000NA4R	STANDARD rectangular
IGPOZ2000NA6R	JUMBO rectangular

Created mainly to host solenoid valves, shutters, hydraulic valves and any other underground tool to inspect. They are manufactured in material resistant to bad weather and knocks. The vandalism-proof bolt and counter-nut act as a handle to lift the cover. The wells allow vehicle passage for maintenance of the greenery and, as a result, they are also indicated for parks, sports fields and public green areas. Equipped with a green cover for good integration with the lawn.

Functions and technical characteristics

- Black base in reinforced polypropylene
- Cover in green reinforced polypropylene
- Vandalism-proof bolt in stainless steel AISI 304 for rectangular models
- Maximum load applicable according to standard UNI EN 124. See table below



EST	
Ref.	description
IGEST2000N14R	STANDARD h 90
IGEST2000N04R	STANDARD h 165
IGEST2000N06R	JUMBO h 165

Extension for rectangular wells; you can insert them in Standard and Jumbo wells in the PCZ and POZ series. They fit on the well to increase its height. They are very useful on sports grounds where the piping is normally placed over 30 cm deep.

Functions and technical characteristics

- Black base in reinforced polypropylene
- No cover

Model	Ref. PCZ - POZ - EST			Max load	Weight kg
	Low. base	Upp. base	H		
MINI	200	160	230	250 kg	0,49
LARGE	320	225	250	450 kg	1,23
STANDARD	380 x 496	273 x 405	300	700 kg	3,66
JUMBO	500 x 640	370 x 520	300	1000 kg	7,18
EST STANDARD	273 x 405	273 x 405	90	-	1,04
EST STANDARD	273 x 405	273 x 405	165	-	1,62
EST JUMBO	370 x 520	370 x 520	165	-	2,50