



# Micro Spray Stake Assemblies



Pre-assembled to save on installation time. Vari-Jet™ models have flow control to adjust radius of throw and reduce flow.

### Features

- Choice of four spray patterns.
- Built-in hole punch.
- Vari-Jet™ Spike assembled with 290 mm off-take tube and 150 mm Rigid Riser.
- Vari-Jet™ Stake assemblies with 290 mm off-take tube on 300 mm stake.
- UV stabilised materials for long life.

### Applications

Home and landscaped gardens.

SPRAYS



Vari-Jet™ Spike  
180° fan



Winged Micro Spray  
Stake Assembly

Vari-Jet™  
Stake Assembly

### Performance Chart - Vari-Jet™ Spike

Pattern			360° x 18	180°	90°
Nozzle Size & Colour	Pressure (kPa)	Flow (lph)	Diameter (m)	Radius (m)	
Vari-Jet™ Spike Red max. 1.5 mm	50	0 - 52	0 - 4.9	0 - 1.9	0 - 1.5
	100	0 - 75	0 - 6.8	0 - 2.4	0 - 2.4
	150	0 - 92	0 - 8.2	0 - 3.0	0 - 2.9
	200	0 - 107	0 - 8.2	0 - 3.2	0 - 3.1
	250	0 - 120	0 - 7.2	0 - 3.4	0 - 3.3

\* Ghosted figures indicate a change of performance from spray to mist.

### Ordering Information - Vari-Jet™ Spike

Spray Pattern	Base Colour	Cap Colour	Order Code	Pack Quantity	Packs per Carton	Carton (kg)
360° x 18 hole	Red	Red	13345	10	14	4.8
180° fan	Red	Blue	13325	10	14	4.8
90° fan	Red	Black	13315	10	14	4.8

### Ordering Information - Winged Micro Spray Stake Assembly (refer page 16 for performance)

Spray Pattern	Base Colour	Cap Colour	Order Code	Pack Quantity	Packs per Carton	Carton (kg)
360° x 18 hole	Blue	Red	17425	25	19	12.4
180° fan	Blue	Blue	17435	25	19	12.4
90° fan	Blue	Black	17445	25	19	12.4
Strip Spray (2 x 20°)	Blue	Black	17455	25	19	12.4

### Ordering Information - Vari-Jet™ Stake Assembly (refer page 14 for performance data)

Spray Pattern	Base Colour	Cap Colour	Order Code	Pack Quantity	Packs per Carton	Carton (kg)
360° x 18 hole	Black	Black	17185	25	16	11.2
180° fan	Black	Black	17195	25	16	11.2
90° fan	Black	Black	17205	25	16	11.2

### Specifications

Dimensions Assembled		Vari-Jet™ Spike	Winged Micro Spray Stake Assembly	Vari-Jet™ Stake Assembly
HEIGHT		355 mm	345 mm	360 mm
WIDTH		55 mm	24 mm	24 mm
WEIGHT (approx.)		32 g	26 g	28 g
UV STABILISED MATERIALS	SPIKE/STAKE	polypropylene	polypropylene	polypropylene
	ADAPTOR	polypropylene	acetal	acetal
	RISER	HDPE	-	-
	KNOB	polypropylene	-	HDPE
	OFF-TAKE TUBE	PVC	PVC	PVC
BASE/CAP		acetal	acetal	acetal
BASE/CONNECTION TYPE: Inlet		BARB 4 mm	BARB 4 mm	BARB 4 mm