



DT-025-50 / DT-025-1000

Micro Distribution Tubing

APPLICATIONS

Extends emitter outlets to desired locations.

FEATURES

- Made of PVC materials

SPECIFICATIONS

Outside diameter: 5,7 mm

Inside diameter: 4 mm

MODELS

DT-025-50: 4-5,7 mm distribution tubing;
15 m coil.

DT-025-1000: 4-5,7 mm distribution tubing;
300 m coil



BF-1, BF-2, BF-3

Barb Transfer Fittings for 4-6 mm Tubing

APPLICATIONS

Used to connect 4-6 mm distribution tubing
(DT-025-50/DT-025-1000).

FEATURES

- Rugged plastic construction
- Pressure: 0 to 3.5 bar

MODELS

BF-1: barb connector for 4-6 tubing

BF-2: barb x barb ell for 4-6 tubing

BF-3: barb x barb x barb tee for 4-6 tubing



TS-025

Tubing Stake

APPLICATIONS

Used for holding 4-6 mm distribution tubing
(DT-025-50/DT-025-1000) in place at the root
zone.

FEATURES

- Constructed of UV-resistant plastic material
- Height: 10 cm

MODEL

TS-025: stake for 4-6 mm tubing



DBC-025

Diffuser Bug Cap

APPLICATIONS

Diffuser for 4-6 mm tubing to minimize soil erosion
at emission point. It also prevents insects and
other debris from clogging 4-6 mm distribution
tubing.

FEATURES

- Barb inlet fits into 4-6 mm distribution tubing
(DT-025-50/DT-025-1000)
- Flanged shield directs water to the desired
location

SPECIFICATIONS

Pressure: 0 to 1.7 bar

MODEL

DBC-025 diffuser for
4-6 mm tubing

