



## MPR SERIES NOZZLES

Plastic nozzles for 1800™ and UNI-Spray™ Series spray heads  
Matched Precipitation Rates for design flexibility

### FEATURES

- Top Color-Coded™ for easy radius and arc identification
- Flow and radius adjustment screw
- Matched Precipitation Rates
- Easily accessible under-the-nozzle filter screen shipped with nozzle
- Convenient re-sealable bags with separate, detachable nozzle and screen pouches

### SPECIFICATIONS

Pressure: 1 to 2.1 bar\*  
Spacing: 0.6 to 4.6 m

### MODELS

5-MPR Series: 5° Trajectory  
8-MPR Series: 10° Trajectory  
10-MPR Series: 15° Trajectory  
12-MPR Series: 30° Trajectory  
15-MPR Series: 30° Trajectory



15-MPR Series Strip: 30° Trajectory  
5-MPR Series Stream Bubbler nozzles:  
0° Trajectory

*\*Rain Bird recommends using 1800 spray heads equipped with PRS system to maintain optimum nozzle performance in higher pressure situations.*

### PERFORMANCE

#### 5-MPR Series

Nozzle	bar	m	m <sup>3</sup> /h	■ mm/h	▲ mm/h
5F	1,0	0,6	0,02	52	60
	1,5	1,0	0,05	47	55
	2,0	1,4	0,08	41	48
	2,1	1,5	0,09	40	46
5H	1,0	0,6	0,01	52	60
	1,5	1,0	0,02	47	55
	2,0	1,4	0,04	41	48
	2,1	1,5	0,05	40	46
5T	1,0	0,6	0,01	52	60
	1,5	1,0	0,02	47	55
	2,0	1,4	0,03	41	48
	2,1	1,5	0,03	40	46
5Q	1,0	0,6	0,01	52	60
	1,5	1,0	0,01	47	55
	2,0	1,4	0,02	41	48
	2,1	1,5	0,02	40	46

#### 8-MPR Series

Nozzle	bar	m	m <sup>3</sup> /h	■ mm/h	▲ mm/h
8F	1,0	1,5	0,12	52	60
	1,5	1,9	0,16	47	55
	2,0	2,3	0,22	41	48
	2,1	2,4	0,23	40	46
8H	1,0	1,5	0,06	52	60
	1,5	1,9	0,09	47	55
	2,0	2,3	0,11	41	48
	2,1	2,4	0,12	40	46
8T	1,0	1,5	0,04	52	60
	1,5	1,9	0,06	47	55
	2,0	2,3	0,07	41	48
	2,1	2,4	0,08	40	46
8Q	1,0	1,5	0,03	52	60
	1,5	1,9	0,04	47	55
	2,0	2,3	0,05	41	48
	2,1	2,4	0,06	40	46

#### 10-MPR Series

Nozzle	bar	m	m <sup>3</sup> /h	■ mm/h	▲ mm/h
10F	1,0	2,1	0,26	58	67
	1,5	2,4	0,29	50	58
	2,0	3,0	0,35	39	45
	2,1	3,1	0,36	37	43
10H	1,0	2,1	0,13	58	67
	1,5	2,4	0,14	50	58
	2,0	3,0	0,18	39	45
	2,1	3,1	0,18	37	43
10T	1,0	2,1	0,09	58	67
	1,5	2,4	0,10	50	58
	2,0	3,0	0,12	39	45
	2,1	3,1	0,12	37	43
10Q	1,0	2,1	0,06	58	67
	1,5	2,4	0,07	50	58
	2,0	3,0	0,09	39	45
	2,1	3,1	0,09	37	43

#### 12-MPR Series

Nozzle	bar	m	m <sup>3</sup> /h	■ mm/h	▲ mm/h
12F	1,0	2,7	0,40	55	63
	1,5	3,2	0,48	47	54
	2,0	3,6	0,59	46	53
	2,1	3,7	0,60	44	51
12TQ	1,0	2,7	0,30	55	63
	1,5	3,2	0,36	47	54
	2,0	3,6	0,45	46	53
	2,1	3,7	0,45	44	51
12H	1,0	2,7	0,20	55	63
	1,5	3,2	0,24	47	54
	2,0	3,6	0,30	46	53
	2,1	3,7	0,30	44	51
12T	1,0	2,7	0,13	55	63
	1,5	3,2	0,16	47	54
	2,0	3,6	0,20	46	53
	2,1	3,7	0,20	44	51
12Q	1,0	2,7	0,10	55	63
	1,5	3,2	0,12	47	54
	2,0	3,6	0,15	46	53
	2,1	3,7	0,15	44	51

#### 15-MPR Series

Nozzle	bar	m	m <sup>3</sup> /h	■ mm/h	▲ mm/h
15F	1,0	3,4	0,60	52	60
	1,5	3,9	0,72	47	55
	2,0	4,5	0,84	41	48
	2,1	4,6	0,84	40	46
15TQ	1,0	3,4	0,45	52	60
	1,5	3,9	0,54	47	55
	2,0	4,5	0,63	41	48
	2,1	4,6	0,63	40	46
15H	1,0	3,4	0,30	52	60
	1,5	3,9	0,36	47	55
	2,0	4,5	0,42	41	48
	2,1	4,6	0,42	40	46
15T	1,0	3,4	0,20	52	60
	1,5	3,9	0,24	47	55
	2,0	4,5	0,28	41	48
	2,1	4,6	0,28	40	46
15Q	1,0	3,4	0,15	52	60
	1,5	3,9	0,18	47	55
	2,0	4,5	0,21	41	48
	2,1	4,6	0,21	40	46

#### 15-MPR Series Strip

Nozzle	bar	W x L (m)	m <sup>3</sup> /h
15EST	1,0	1,2 x 4,0	0,10
	1,5	1,2 x 4,3	0,11
	2,0	1,2 x 4,3	0,13
	2,1	1,2 x 4,6	0,14
15CST	1,0	1,2 x 7,9	0,20
	1,5	1,2 x 8,5	0,23
	2,0	1,2 x 8,5	0,25
	2,1	1,2 x 9,2	0,27
15SST	1,0	1,2 x 7,9	0,20
	1,5	1,2 x 8,5	0,23
	2,0	1,2 x 8,5	0,25
	2,1	1,2 x 9,2	0,27
9SST	1,0	2,7 x 4,9	0,30
	1,5	2,7 x 4,9	0,33
	2,0	2,7 x 5,5	0,36
	2,1	2,7 x 5,5	0,39

#### 5-MPR Series Stream Bubbler

Nozzle	bar	m	m <sup>3</sup> /h
5F-B	1,0	1,5	0,35
	1,5	1,5	0,35
	2,0	1,5	0,35
	2,1	1,5	0,35
5H-B	1,0	1,5	0,23
	1,5	1,5	0,23
	2,0	1,5	0,23
	2,1	1,5	0,23
5Q-B	1,0	1,5	0,12
	1,5	1,5	0,12
	2,0	1,5	0,12
	2,1	1,5	0,12
5CST-B	1,0	1,5	0,12
	1,5	1,5	0,12
	2,0	1,5	0,12
	2,1	1,5	0,12

Flow at adjusted radius of 1.5 m



Square nozzle spacing based on head-to-head throw (m)

W = Width of coverage pattern

L = Length of coverage pattern

#### Nozzles

Note: radius reduction over 25% of the normal throw of the nozzle is not recommended

■ 50%

▲ 50%