

Suction and delivery ~ Multi-purpose



SPIRABEL® GMDS

+60
°C
-15

Multipurpose hose

Reinforced with a white, rigid and shock-proof PVC spiral in a soft PVC wall.



- 1 Shockproof spiral reinforcement
- 2 Flexible PVC green wall

APPLICATIONS

Multi purpose

ALL SECTORS OF ACTIVITY

Marking : Ø inn [batch number] [code date]

mm	± mm	mm	g/m	Bar	Bar	V mbar	mm	Green opaque 30 m
25	+/- 0,6	3,0	349	15	5	700	60	033207
32	+/- 0,6	3,1	456	15	5	600	75	034380
38	+/- 0,6	3,5	553	15	5	600	90	034383
51	+/- 0,6	4,2	777	15	5	600	95	033233
63	+/- 0,6	4,3	1019	12	5	500	115	034193
76	+/- 0,6	4,8	1295	12	5	500	120	033255
89	+/- 0,6	6,1	1725	9	3	500	150	033905
102	+/- 0,6	6,1	2048	9	3	500	180	033920
127	+/- 0,6	6,3	2909	9	3	500	300	033951
152	+/- 0,6	6,3	4319	9	3	500	320	148914

ADVANTAGES

Spirabel GMDS is a resistant, flexible and economic hose. Its very smooth internal wall reduces the flow losses.

CONNECTORS

Guillemin or Storz symmetrical connectors, cam or universal joint connectors – Fixings with single-thread or spiral collars (SERFLEX). Crimping and band collars are not recommended as they do not ensure a perfect leak proof connection and increase the risk of the spiral being crushed and breaking.

CHEMICAL RESISTANCE

See table pages 69 to 72 column A.

We recommend to use SPIRAFUEL or SPIRABEL PUA2 for the transfer of hydrocarbons.

WARNING

Spiral hoses have in general an elongation under pressure that can be important when temperature is above 40°C. This has to be considered before installation.

We remain at your disposal for any question on this issue.