

PRO ADJUSTABLE NOZZLES

Choose Pro Adjustable Nozzles for optimal landscape coverage in any setting.

KEY BENEFITS

- Adjustable from 0° to 360° for maximum design flexibility
- Easy-grip top for simple adjustment
- Strong edges for a defined pattern with better wind resistance
- Large water droplets minimise misting with better uniformity

ADDITIONAL FEATURES

- Matched precipitation rate on each nozzle from 8A to 17A
- Even distribution results in better coverage
- Colour-coded for easy field identification

OPERATING SPECIFICATIONS

- Recommended operating pressure: 2.1 bar; 210 kPa
- Pair with Pro-Spray PRS30 pop-up for pressure regulation to 2.1 bar; 210 kPa
- Warranty period: 2 years



4A Nozzle
Radius: 1.2 m



6A Nozzle
Radius: 1.8 m



8A Nozzle
Radius: 2.4 m



10A Nozzle
Radius: 3.0 m



12A Nozzle
Radius: 3.7 m



15A Nozzle
Radius: 4.6 m



17A Nozzle
Radius: 5.2 m

Pro Adjustable Nozzle



PRO ADJUSTABLE NOZZLES PERFORMANCE DATA



4A 1.2 m radius
Adjustable from 0° to 360°
● Lt. Green Trajectory: 0°

6A 1.8 m radius
Adjustable from 0° to 360°
● Lt. Blue Trajectory: 0°

8A 2.4 m radius
Adjustable from 0° to 360°
● Brown Trajectory: 0°

Arc	Pressure		Radius m	Flow		Precip mm/hr		Radius m	Flow		Precip mm/hr		Radius m	Flow		Precip mm/hr	
	bar	kPa		m ³ /hr	l/min	■	▲		m ³ /hr	l/min	■	▲		m ³ /hr	l/min	■	▲
45° ▶	1.0	100	0.9	0.02	0.31	187	216	1.5	0.03	0.54	117	136	2.0	0.04	0.62	77	89
	1.5	150	1.0	0.02	0.39	178	206	1.6	0.04	0.60	108	124	2.2	0.04	0.72	72	83
	2.1	210	1.2	0.03	0.48	167	193	1.8	0.04	0.65	98	114	2.4	0.05	0.83	67	77
	2.5	250	1.3	0.03	0.56	158	183	1.9	0.04	0.70	92	106	2.6	0.05	0.91	63	73
	3.0	300	1.4	0.04	0.64	149	172	2.1	0.05	0.75	86	99	2.9	0.06	1.01	59	68
90° ◑	1.0	100	0.9	0.04	0.72	213	246	1.5	0.06	1.08	116	134	2.0	0.07	1.24	77	89
	1.5	150	1.0	0.05	0.76	182	210	1.6	0.07	1.21	109	126	2.2	0.09	1.44	72	83
	2.1	210	1.2	0.05	0.83	139	160	1.8	0.08	1.35	102	118	2.4	0.10	1.65	67	77
	2.5	250	1.3	0.05	0.91	129	149	1.9	0.09	1.47	97	112	2.6	0.11	1.82	63	73
	3.0	300	1.4	0.06	0.95	116	134	2.1	0.10	1.61	92	106	2.9	0.12	2.02	59	68
120° ◐	1.0	100	0.9	0.06	0.97	221	255	1.5	0.08	1.26	102	118	2.0	0.10	1.66	77	89
	1.5	150	1.0	0.07	1.10	188	217	1.6	0.09	1.43	97	112	2.2	0.11	1.92	72	83
	2.1	210	1.2	0.07	1.25	162	187	1.8	0.10	1.61	91	105	2.4	0.13	2.20	67	77
	2.5	250	1.3	0.08	1.36	146	168	1.9	0.11	1.76	87	100	2.6	0.15	2.43	63	73
	3.0	300	1.4	0.09	1.49	131	151	2.1	0.12	1.93	82	95	2.9	0.16	2.69	59	68
180° ◓	1.0	100	0.9	0.07	1.18	178	206	1.5	0.10	1.70	92	106	2.0	0.15	2.49	77	89
	1.5	150	1.0	0.08	1.38	157	181	1.6	0.12	1.96	88	102	2.2	0.17	2.87	72	83
	2.1	210	1.2	0.10	1.60	139	160	1.8	0.13	2.24	84	97	2.4	0.20	3.30	67	77
	2.5	250	1.3	0.11	1.78	127	146	1.9	0.15	2.47	81	94	2.6	0.22	3.65	63	73
	3.0	300	1.4	0.12	1.98	115	133	2.1	0.16	2.72	78	90	2.9	0.24	4.03	59	68
240° ◒	1.0	100	0.9	0.12	1.94	220	254	1.5	0.15	2.44	99	114	2.0	0.20	3.32	77	89
	1.5	150	1.0	0.13	2.24	192	221	1.6	0.17	2.83	96	111	2.2	0.23	3.83	72	83
	2.1	210	1.2	0.16	2.59	168	194	1.8	0.20	3.28	92	107	2.4	0.26	4.40	67	77
	2.5	250	1.3	0.17	2.86	153	177	1.9	0.22	3.63	89	103	2.6	0.29	4.86	63	73
	3.0	300	1.4	0.19	3.17	139	160	2.1	0.24	4.03	86	99	2.9	0.32	5.38	59	68
270° ◑	1.0	100	0.9	0.13	2.09	211	244	1.5	0.18	3.08	111	128	2.0	0.22	3.73	77	89
	1.5	150	1.0	0.14	2.40	183	211	1.6	0.21	3.52	106	122	2.2	0.26	4.31	72	83
	2.1	210	1.2	0.16	2.75	159	183	1.8	0.24	4.02	101	116	2.4	0.30	4.95	67	77
	2.5	250	1.3	0.18	3.02	144	166	1.9	0.27	4.42	97	112	2.6	0.33	5.47	63	73
	3.0	300	1.4	0.20	3.33	130	150	2.1	0.29	4.87	92	107	2.9	0.36	6.05	59	68
360° ●	1.0	100	0.9	0.14	2.26	171	197	1.5	0.21	3.57	96	111	2.0	0.30	4.97	77	89
	1.5	150	1.0	0.16	2.60	148	171	1.6	0.24	4.07	92	106	2.2	0.34	5.75	72	83
	2.1	210	1.2	0.18	2.98	129	149	1.8	0.28	4.62	87	100	2.4	0.40	6.61	67	77
	2.5	250	1.3	0.20	3.29	117	135	1.9	0.30	5.06	83	96	2.6	0.44	7.29	63	73
	3.0	300	1.4	0.22	3.63	106	122	2.1	0.33	5.56	79	92	2.9	0.48	8.07	59	68

Bold = Recommended pressure

Note: The Pro-Spray PRS30's built-in pressure regulator controls output to a maximum of 2.1 bar; 210 kPa. Adjusting the radius reduction screw may be required to achieve catalogue radius and flow.

PRO ADJUSTABLE NOZZLES PERFORMANCE DATA



10A 3.0 m radius
Adjustable from 0° to 360°
● Red Trajectory: 15°



12A 3.7 m radius
Adjustable from 0° to 360°
● Green Trajectory: 28°



15A 4.6 m radius
Adjustable from 0° to 360°
● Black Trajectory: 28°

Arc	Pressure		Radius m	Flow		Precip mm/hr		Radius m	Flow		Precip mm/hr		Radius m	Flow		Precip mm/hr	
	bar	kPa		m ³ /hr	l/min	■	▲		m ³ /hr	l/min	■	▲		m ³ /hr	l/min	■	▲
45° ▶	1.0	100	2.6	0.04	0.68	49	56	3.2	0.04	0.73	34	40	4.0	0.08	1.27	38	43
	1.5	150	2.8	0.05	0.80	49	57	3.4	0.06	0.97	40	46	4.3	0.09	1.51	39	45
	2.1	210	3.0	0.06	0.94	49	56	3.7	0.07	1.23	44	51	4.6	0.11	1.79	40	46
	2.5	250	3.2	0.06	1.06	48	56	3.9	0.09	1.44	46	54	4.9	0.12	2.00	40	46
	3.0	300	3.5	0.07	1.18	47	54	4.1	0.10	1.68	48	56	5.2	0.14	2.25	40	46
90° ◐	1.0	100	2.6	0.08	1.35	49	56	3.2	0.09	1.46	34	40	4.0	0.15	2.53	38	43
	1.5	150	2.8	0.10	1.61	49	57	3.4	0.12	1.93	40	46	4.3	0.18	3.03	39	45
	2.1	210	3.0	0.11	1.89	49	56	3.7	0.15	2.46	44	51	4.6	0.21	3.57	40	46
	2.5	250	3.2	0.13	2.11	48	56	3.9	0.17	2.88	46	54	4.9	0.24	4.01	40	46
	3.0	300	3.5	0.14	2.37	47	54	4.1	0.20	3.36	48	56	5.2	0.27	4.50	40	46
120° ◑	1.0	100	2.6	0.11	1.80	49	56	3.2	0.12	1.94	34	40	4.0	0.20	3.38	38	43
	1.5	150	2.8	0.13	2.14	49	57	3.4	0.15	2.58	40	46	4.3	0.24	4.03	39	45
	2.1	210	3.0	0.15	2.52	49	56	3.7	0.20	3.28	44	51	4.6	0.29	4.76	40	46
	2.5	250	3.2	0.17	2.82	48	56	3.9	0.23	3.84	46	54	4.9	0.32	5.34	40	46
	3.0	300	3.5	0.19	3.16	47	54	4.1	0.27	4.48	48	56	5.2	0.36	6.00	40	46
180° ◒	1.0	100	2.6	0.16	2.71	49	56	3.2	0.17	2.91	34	40	4.0	0.30	5.07	38	43
	1.5	150	2.8	0.19	3.21	49	57	3.4	0.23	3.86	40	46	4.3	0.36	6.05	39	45
	2.1	210	3.0	0.23	3.78	49	56	3.7	0.30	4.92	44	51	4.6	0.43	7.14	40	46
	2.5	250	3.2	0.25	4.23	48	56	3.9	0.35	5.76	46	54	4.9	0.48	8.02	40	46
	3.0	300	3.5	0.28	4.73	47	54	4.1	0.40	6.71	48	56	5.2	0.54	9.00	40	46
240° ◓	1.0	100	2.6	0.22	3.61	49	56	3.2	0.23	3.88	34	40	4.0	0.41	6.76	38	43
	1.5	150	2.8	0.26	4.28	49	57	3.4	0.31	5.15	40	46	4.3	0.48	8.07	39	45
	2.1	210	3.0	0.30	5.03	49	56	3.7	0.39	6.56	44	51	4.6	0.57	9.52	40	46
	2.5	250	3.2	0.34	5.64	48	56	3.9	0.46	7.68	46	54	4.9	0.64	10.69	40	46
	3.0	300	3.5	0.38	6.31	47	54	4.1	0.54	8.95	48	56	5.2	0.72	12.00	40	46
270° ◔	1.0	100	2.6	0.24	4.06	49	56	3.2	0.26	4.37	34	40	4.0	0.46	7.60	38	43
	1.5	150	2.8	0.29	4.82	49	57	3.4	0.35	5.80	40	46	4.3	0.54	9.08	39	45
	2.1	210	3.0	0.34	5.66	49	56	3.7	0.44	7.38	44	51	4.6	0.64	10.71	40	46
	2.5	250	3.2	0.38	6.34	48	56	3.9	0.52	8.65	46	54	4.9	0.72	12.03	40	46
	3.0	300	3.5	0.43	7.10	47	54	4.1	0.60	10.07	48	56	5.2	0.81	13.50	40	46
360° ◕	1.0	100	2.6	0.32	5.41	49	56	3.2	0.35	5.83	34	40	4.0	0.61	10.13	38	43
	1.5	150	2.8	0.39	6.43	49	57	3.4	0.46	7.73	40	46	4.3	0.73	12.10	39	45
	2.1	210	3.0	0.45	7.55	49	56	3.7	0.59	9.84	44	51	4.6	0.86	14.28	40	46
	2.5	250	3.2	0.51	8.45	48	56	3.9	0.69	11.53	46	54	4.9	0.96	16.03	40	46
	3.0	300	3.5	0.57	9.47	47	54	4.1	0.81	13.43	48	56	5.2	1.08	18.00	40	46

Bold = Recommended pressure

Note: The Pro-Spray PRS30's built-in pressure regulator controls output to a maximum of 2.1 bar; 210 kPa. Adjusting the radius reduction screw may be required to achieve catalogue radius and flow.

PRO ADJUSTABLE NOZZLES PERFORMANCE DATA



17A 5.2 m radius
Adjustable from 0° to 360°
● Grey Trajectory: 28°

Arc	Pressure		Radius m	Flow		Precip mm/hr	
	bar	kPa		m ³ /hr	l/min	■	▲
45° ▶	1.0	100	4.6	0.10	1.68	38	43
	1.5	150	4.9	0.12	1.94	38	44
	2.1	210	5.2	0.13	2.23	39	45
	2.5	250	5.5	0.15	2.46	39	45
	3.0	300	5.8	0.16	2.72	39	45
90° ◑	1.0	100	4.6	0.20	3.36	38	43
	1.5	150	4.9	0.23	3.88	38	44
	2.1	210	5.2	0.27	4.45	39	45
	2.5	250	5.5	0.30	4.92	39	45
	3.0	300	5.8	0.33	5.44	39	45
120° ◐	1.0	100	4.6	0.27	4.48	38	43
	1.5	150	4.9	0.31	5.17	38	44
	2.1	210	5.2	0.36	5.94	39	45
	2.5	250	5.5	0.39	6.56	39	45
	3.0	300	5.8	0.43	7.25	39	45
180° ◕	1.0	100	4.6	0.40	6.71	38	43
	1.5	150	4.9	0.47	7.75	38	44
	2.1	210	5.2	0.53	8.91	39	45
	2.5	250	5.5	0.59	9.83	39	45
	3.0	300	5.8	0.65	10.87	39	45
240° ◔	1.0	100	4.6	0.54	8.95	38	43
	1.5	150	4.9	0.62	10.34	38	44
	2.1	210	5.2	0.71	11.88	39	45
	2.5	250	5.5	0.79	13.11	39	45
	3.0	300	5.8	0.87	14.50	39	45
270° ◓	1.0	100	4.6	0.60	10.07	38	43
	1.5	150	4.9	0.70	11.63	38	44
	2.1	210	5.2	0.80	13.36	39	45
	2.5	250	5.5	0.89	14.75	39	45
	3.0	300	5.8	0.98	16.31	39	45
360° ●	1.0	100	4.6	0.81	13.43	38	43
	1.5	150	4.9	0.93	15.51	38	44
	2.1	210	5.2	1.07	17.82	39	45
	2.5	250	5.5	1.18	19.67	39	45
	3.0	300	5.8	1.30	21.75	39	45

Bold = Recommended pressure

Note: The Pro-Spray PRS30's built-in pressure regulator controls output to a maximum of 2.1 bar; 210 kPa. Adjusting the radius reduction screw may be required to achieve catalogue radius and flow.